


DomoStep®

The platform featuring the quickest installation

MADE IN ITALY



Remote control
(included)

TECHNICAL SPECIFICATIONS

Traction/drive	Screw driven
Machine room	No
Installation	Outdoor and indoor
Power Supply	Single phase, 230 Vac - 50/60 Hz
Duty load	315 Kg
Speed	4 cm/s
Travel	350 mm Min - 1300 mm Max
Entrances	Opposite
Stops	2 max.
Headroom	2000 mm min.
Pit	Not required (<i>mobile fall arrest ramp</i>)
Operation	Manual, hold-to run
Electric panel	Integrated into the machine
Travel shaft	No
Noise level (*)	Less than 50 dB
Rated power/Motor	6W (<i>in stand-by</i>)
Power consumption	46W (<i>during normal use</i>)
Cycles/hour	4 max (<i>in continuous cycle</i>)
Operating temperatures	-5°C/+40°C
Reference standards	M.D.2006/42/EC

SAFETY SYSTEMS

Emergency STOP switch
Protection bellows (<i>opzionale</i>)
Automatic emergency descent in case of blackout
Sound alarm button
ON/OFF disabling key in platform
Batteries for operation without power supply (<i>10 cycles max</i>)
Automatic fall arrest bar
Blind BL side parapet (<i>optional</i>)
Aluminium fall arrest lamp
Fixed safety handle

CAR/PLATFORM

Open platform without walls	
Available dimensions	(LxD) 900x1250 - 900x1400 - 800x1250 (<i>special</i>)

LANDING DOORS

Glazed GL one-leaf gate (<i>standard</i>) - Blind BL (<i>optional</i>)
--

(*) Measured from 1.00 m away and with 250 kg of load.

- The safety arm and the drop-down ramp **can be reversed on site**
- **No machine room** with panel integrated into the machine body
- **Pre-assembled** and pre-wired machine supplied in a single (stackable) package
- Open platform with **parapet and automatic protection arm**